

Heritage Garages



Extended roof construction (shown left) links garages with dwelling to identify entry to the garage forecourt. Heritage 8 multiple units for Wates Built Homes limited.



Gable end cladding in brick co-ordinates these garages with the adjacent house development. Garages are stepped to accommodate the site levels.





SPARI ITE



WHITESPAR





COTSWOLD STONE



BRICK EFFECT - FRONT POSTS ONLY



Heritage 9 garages with Marley Modern roof tiles, Marley dry ridge and dry verge, cedar vertically boarded doors and Whitespar natural stone granule wall finish.

HERITAGE GARAGES

Although designed to complement current style development, Heritage Garages will blend with any mature property.

Roofed in the traditional way with Marley Roof Tiles, these garages are available in a variety of finishes, two widths and two lengths.

The superior specification includes choice of up-and-over doors and option of brick effect fron posts.

Rapid on-site construction and strightforward foundations make Heritage Garages highly cost effective both in material and supervisory terms.

Heritage Garages

Walls

Interlocking precast concrete panels with an applied aggregate finish externally. Manufactured to CP116 with a steel reinforcement to BS4449, these panels are non-combustible and satisfy the structural integrity and flame penetration requirements of BS476 Part 1 1953 for half an hour. Connecting bolts and other fitting are rust resistant with external bolt heads concealed and the joints between panels sealed with mastic.

Roof

Marley interlocking roof tiles, to a colour and profile selected by customer, carried on felt and battens supported by timber purlins. Interlocking concrete roof tiles or profiled steel lightweight simulated roof tiles from other manufacturers can be specified where suitable for a roof pitch of 30°.

Doors

Factory primed galvanised steel up-and-over doors, with a choice of horizontal or vertical profile, or Regency style, are supplied as standard. All doors are supplied with a locking handle and will soon be available with security Eurolocks fitted as standard.

Rainwater Guttering

Dimensions

Black vinyl half round guttering and downpipes are supplied as standard.

Accessories

WINDOWS: Aluminium framed window with white polyester finish, incorporating full width opening fanlight, gasket glazed prior to delivery. Size 851mm high x 813mm wide (2'9112" x 2'8"0 overall.)

PERSONAL DOORS: Galvanised steel door soon available vertically profiled as standard with security Eurolock, set in a steel frame and primed ready for painting. Operation is outward opening, left or right hung, viewed from outside. Size 1.981m high x 813mm wide (6'6" x 2'8") overall. Alternatively, a Western Red Cedarwood door, part glazed, framed, ledged and braced with shiplap boarding is available. Supplied with lock, handle and glass. Size as above.

Site Preparation

A flat and level concrete base (with steps when necessary) is required. Please ask for base layout drawings showing pocket details for gale posts.

Services

PLANS: Elevation drawings, suitable for submission to the Local Authority, are available on request.

CONSTRUCTION: Heritage Garages are constructed nationwide using company trained teams. If assistance is required with planning a Heritage Garage layout we will be pleased to arrange for our Area Sales Manager to call by appointment.

Model		Heritage 8	Heritage 8 Brick Front	Heritage 9
Length	External Internal*	First Bay Additional Bay 2.616m (8'7") 2.515m(8'3") 2.438m (8'0")	First Bay Additional Bay 2.616m (8'7") 2.515m(8'3") 2.438m (8'0")	First Bay Additional Bay 3.02m (9'11") 2.921m(9'7") 2.845m (9'4")
Length	External Internal	Standard Length	(16'8½") Extra Length (16'2½")	5.969m (19'7") 5.815m (19'1")
Door	External 'Drive through' clearance	Height Width 1.981m (6'6") 2.286m (7'6") 1.880m (6'2") 2.184m (7'2")	Height Width 1.981m (6'6") 2.286m (7'6") 1.880m (6'2") 2.184m (7'2")	Height Width 1.981m (6'6") 2.692m (8'10") 1.880m (6'2") 2.591m (8'6")

Steps

Steps of 152mm (6") can be incorporated in blocks of heritage Garages - left or right handed to suit site.

Finishes

Applied aggregate finish in a choice of 'Sparlite', 'Buff Quartz', 'Whitespar', or 'Brownstone' as standard. Structural ties to either gale end or to the rear elevation can be provided for complete or part cladding in brickwork, by a building contractor. In this way, adjacent house bricks can be matched or wall and landscape features can be introduced to coordinate the garages with other design elements of the scheme.

Leofric Building Systems Ltd

Hillside House, Stratford Road, Mickleton, Nr. Chipping Campden, Glos GL55 6SR

Tel: 01386 430 121 Fax: 01386 438 135 Email: sales@leofricbuildings.co.uk Website: www.leofricbuildings.co.uk